



SPECIALIZED CONCEPT (PTY) LTD

3 Tile Crescent, Clayville, South Africa

CUSTOM 4x4 MRAP VEHICLE



NOTE: PICTURES SHOWN ARE FOR REFERENCE ONLY. FINAL PRODUCTION WILL BE BASED ON END USER REQUEST.

TECHNICAL SPECIFICATIONS

GENERAL SPECIFICATIONS

• Crew	2+8
• Kerb Weight	15 500 kg
• Payload	4 000 kg
• Wheelbase	3.6 m
• Hull	Monocoque
• Max Speed	110 km/h
• Turning Circle	17 m
• Road Range	Turbo Charged Diesel 6-cylinder, Intercooled 336 Kw, 1627 nm
• Power to Weight	21.6 kW/t
• Transmission	6-Speed automatic
• Difflocks	Air operated front, centre and rear
• Brakes	Pneumatic, Disc, ABS Standard
• Tyres	16.00 R20
• Air Conditioning	12 Kw
• Electrical System	24 v
• Ballistic Protection	Stanag 4569 level 3
• Blast Protection	Stanag 4569 level 4a & 4b

An MRAP vehicle, prioritises mission effectiveness, troop safety, and high performance. With versatile operational capabilities for security, confrontations, reconnaissance, and warfare, it features 2 side doors for increased driver and turret operator mobility. Enhanced with ballistic protection at STANAG 4569 Level 3 and robust blast protection at STANAG 4569 Level 4a & 4b, the Custom MRAP 4x4 ensures superior defense capabilities.

OPTIONS

- Run Flat Inserts
- Central Tyre Inflation System
- Radio, Intercom System
- Battlefield Management System
- Winch
- NATO Standard Tow Hitch
- Public Address System
- Fire Suppression System
- Various Manual-and Remote Operated Turret Systems
- Vehicle Location and Tracking System
- Driver Assist Camera System